Appl. No. 10/714,012 Amdt. dated June 21, 2005 Reply to Office action of March 21, 2005

In the Claims:

No claims are amended herein.

1. (original) A fixture adapted to combine with a drum stand which has a bracket having two legs extending out from the bracket, a paddle having a first distal end connected to the drum stand and a base having a first distal end connected to the bracket and a second distal end securely connected to the paddle, the fixture comprising:

a pair of rods threadingly extendable into opposite sides of the first distal end of the base, a pair of ribs adapted to be formed on opposite sides of the base, a pair of guiding grooves adapted to be oppositely defined in a bottom portion of the bracket of the drum stand to correspond to and receive therein the pair of ribs and a pair of notches adapted to be oppositely defined in a mediate portion of the bracket of the drum stand to correspond to and receive therein the pair of rods.

- 2. (original) The fixture as claimed in claim 1, wherein the pair of rods are threaded bolts.
- 3. (original) A fixture adapted to combine with a drum stand which has a bracket having two legs extending out from the bracket, a paddle having a first distal end connected to the drum stand and a base having a first distal end connected to the

Page 2 — RESPONSE (U.S. Patent Appln. S.N. 10/714,012) [\\Files\files\Correspondence\Jume 2005\t1276rtoa062105.doc]

Appl. No. 10/714,012 Amdt. dated June 21, 2005 Reply to Office action of March 21, 2005

bracket and a second distal end securely connected to the paddle, the fixture comprising:

a pair of guiding grooves oppositely defined in a bottom portion of the base, a pair of notches oppositely defined in a mediate portion of the base, a pair of ribs formed on a bottom portion of the bracket to correspond to and receive therein the ribs and a pair of rods formed on a mediate portion of the bracket to correspond to and receive therein the notches.

4. (original) The fixture as claimed in claim 3, wherein the pair of rods are threaded bolts.